



High Voltage Silicone Rubber Lead Wire 200°C VW-1



Description: One conductor stranded copper, extruded flexible rubber insulation overall.
Constructions to UL-3239 (150°C) and nickel plated copper conductor are available.

DABURN Cat. No.	AWG	Strand	Nom. Ins. Wall	D.C.Volt Rating	Nom. O.D.
2636/22A	22	7/30	.045	20KV	.120
2636/22B	22	7/30	.062	25KV	.155
2636/22C	22	7/30	.075	30KV	.180
2636/22D	22	7/30	.097	40KV	.225
2636/20A	20	10/30	.045	20KV	.126
2636/20B	20	10/30	.062	25KV	.160
2636/20C	20	10/30	.075	30KV	.186
2636/20D	20	10/30	.097	40KV	.232
2636/18A	18	16/30	.045	20KV	.136
2636/18B	18	16/30	.062	25KV	.170
2636/18C	18	16/30	.075	30KV	.196
2636/18D	18	16/30	.097	40KV	.245
2636/16A	16	26/30	.045	20KV	.150
2636/16B	16	26/30	.062	25KV	.185
2636/16C	16	26/30	.075	30KV	.210
2636/16D	16	26/30	.097	40KV	.256
2636/14A	14	41/30	.045	20KV	.167
2636/14B	14	41/30	.062	25KV	.200
2636/14C	14	41/30	.075	30KV	.227
2636/14D	14	41/30	.097	40KV	.275
2636/12A	12	65/30	.045	20KV	.181
2636/12B	12	65/30	.062	25KV	.215
2636/12C	12	65/30	.075	30KV	.241
2636/12D	12	65/30	.097	40KV	.290
2636/10A	10	105/30	.045	20KV	.220
2636/10B	10	105/30	.062	25KV	.255
2636/10C	10	105/30	.075	30KV	.280
2636/10D	10	105/30	.097	40KV	.325

Standard Put-Up: 100 Ft., 1000 Ft.

Standard Color: White (natural.) Additional colors available to order.

For your own free copy of our complete catalog send us [E-mail](#).

Back to [New Products](#).

Back to [Overview](#).

Back to DABURN'S [Home Page](#).

Daburn electronics & cable corp.

224 Pegasus Ave.

Northvale, NJ 07647

Tel: 201-768-5400

Fax: 201-768-9642

E-Mail: daburn@daburn.com

URL: <http://www.daburn.com/>