
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

■ 2005, Projects Unlimited Inc.

SPECIFICATIONS		
	VALUES	UNITS
	OMNI	_

PARAMETERS	VALUES	UNITS
DIRECTIVITY	OMNI	_
SENSITIVITY	-35±4	dB
STANDARD OPERATING VOLTAGE	2	Vdc
MAX OPERATING VOLTAGE	10	Vdc
CURRENT CONSUMPTION (MAX)	0.5	mA
IMPEDANCE	2.2	k0hm
SIGNAL TO NOISE RATIO (MIN.)	68	dB
TERMINAL	SOLDER PAD	-
INTERNAL CAPACITOR	33 & 10	pF

REVISIONS				
LTR	DESCRIPTION	DATE	APPROVED	
_	RELEASED FROM ENGINEERING	4/2/14		



NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2011/65/EU COMPLIANT.
- 4. THIS PART IS BACK ELECTRET

POM-3535L-2-R.DWG



3541 Stop Eight Road Dayton, Ohio 45414

APPROVALS		DATE	
DRAWN	M.L.	4/14	H
CHECKED	M.L.	4/14	
APPROVED	R P	1/11	6

DRAWING NO.
POM-3535L-2-R SIZE

B.R. 4/14 SCALE: N.T.S. SHEET 1