

## RJ45 socket insert - CUC-V04-BU-180 - 1407409

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

RJ45 socket insert, 1-way, for PCB mounting, CAT5e, 8-pos., shielded, with straight solder pins (THT)



### Key commercial data

Packing unit	1 pc
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Standards/specifications	IEC 60603-7
Number of positions	8
Connection profile	RJ45 8(8)
Insertion/withdrawal cycles	≥ 750
Connection method	THT

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP20

#### Material data

Inflammability class according to UL 94	V0
---	----

#### Electrical characteristics

Number of positions	8
Nominal voltage $U_N$	125 V AC
Nominal current $I_N$	1.5 A

## RJ45 socket insert - CUC-V04-BU-180 - 1407409

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440312

#### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC002641

#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501