

Acoustic element - PSD-S AE SC1-2 105DB - 2700139

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Siren element, alternating, 24 V DC, max. 105 dB(A), black

Product Features

- ✓ High volume ensures optimum awareness even in noisy environments
- ✓ Alternating continuous tone ensures optimum awareness



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	100.0 GRM
Custom tariff number	85318095
Country of origin	Germany

Technical data

Dimensions

Diameter	70 mm
Height	79 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Degree of protection	IP40, when installed

General

Material	Polycarbonate PC
Color	black
Weight	106 g
Mounting position	any

Electrical data

Acoustic element - PSD-S AE SC1-2 105DB - 2700139

Technical data

Electrical data

Input voltage	24 V DC
Maximum inrush current	max. 500 mA
Current consumption	150 mA
Service life, electrical	min. 5,000 h
Operating time	100 %
Type of acoustic signal	Continuous tone, alternating
Tone frequency	approx. 2.5 kHz
	approx. 3.5 kHz
Volume	105 dB(A)

Approvals / conformities

Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
-------------------------------	--

Classifications

eCl@ss

eCl@ss 4.0	27240208
eCl@ss 4.1	27240208
eCl@ss 5.0	27371214
eCl@ss 5.1	27371214
eCl@ss 6.0	27371214
eCl@ss 7.0	27371214
eCl@ss 8.0	27371214

ETIM

ETIM 3.0	EC001026
ETIM 4.0	EC001026
ETIM 5.0	EC001261

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311

Drawings

Acoustic element - PSD-S AE SC1-2 105DB - 2700139

Dimensioned drawing

