



#### General ordering data

Order No.	1023760000
Part designation	WDU 2.5N OR
Version	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, Polyamide, Orange, TS 35
EAN	4008190060848
Qty.	100 pc(s).

#### Product notes

Note, ordering data	For colours available see section W-series accessories "Specific functions"
Note, technical data	2.5 mm <sup>2</sup> conductor with wire end ferrule plus plastic collar only with collar optimised for diameter (order No. 1333100000, 500 pcs)
Product description	Their small size compared to the respective rated cross-section makes the modular terminals with the compact design very popular.
Note, accessories	Socket and test plug, see section "W-series accessories"

#### PT OKIECEEx/ATEX rating data

EU-type examination certificate	KEMA98ATEX1683U
Download, German	KEMA98ATEX1683U_d.pdf
Download English	KEMA98ATEX1683U_e.pdf
IECEX Certificate of Conformity	IECEXULD05.0008U
Download	IECEXULD05.0008U_e.pdf
ATEX voltage	440 V
ATEX current	21 A
ATEX conductor cross-section	2.5 mm <sup>2</sup>
IECEX voltage	440 V
IECEX current	20 A
IECEX conductor cross-section	2.5 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity

#### PT OKIEEx/ATEX rating data

Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

#### 2 clampable conductors (H05V/H07V) with equal cross-section (rated connection)

Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	1.5 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	1.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	1.5 mm <sup>2</sup>

#### Additional technical data

Colour of insulating material	Orange
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	Yes
Installation advice	TS 35
Insulating material	Polyamide
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	W-Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Feed-through terminal

#### CSA rating data

Voltage (CSA)	300 V
CSA current	20 A
Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 12

#### Conductors for clamping (rated connection)

Clamping range, min.	0.05 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Stripping length	10 mm
Clamping screw	M 2.5
Blade size	0.6 x 3.5 mm
Tightening torque range	0.4...0.6 Nm
Torque level with DMS electric screwdriver	1
Gauge to IEC 60947-1	A3
Solid, min.	0.5 mm <sup>2</sup>

#### Conductors for clamping (rated connection)

Solid, max.	4 mm <sup>2</sup>
Stranded, min.	1.5 mm <sup>2</sup>
Stranded, max.	4 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	4 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	2.5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	2.5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	1.5 mm <sup>2</sup>
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 12
AWG conductor size, min.	0.13 mm <sup>2</sup>
AWG conductor size, max.	3.31 mm <sup>2</sup>

#### Dimensions

Width	5.1 mm
Height of lowest version	37.5 mm
Length	44 mm
Weight	6.2 g
TS 35 offset	24.5 mm

#### Disconnect terminals

Torque level with DMS electric screwdriver	1
--	---

#### Rating data

Rated cross-section	2.5 mm <sup>2</sup>
Rated voltage	500 V
Rated impulse voltage	6 kV
Rated current	24 A
Standards	IEC 60947-7-1
Current with max. conductor	32 A
Pollution severity	3

#### UL rating data

Voltage (UL)	300 V
Current (UL)	10 A
Min. cross-section (UL)	AWG 30
Max. cross-section (UL)	AWG 12

## Approvals

Approvals institutes



## Classifications

eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

## Similar products

Order No.	Part designation	Version
1023700000	WDU 2.5N	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1023780000	WDU 2.5N BL	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, Wemid, blue, TS 35
1023720000	WDU 2.5N GN WAP GE	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, Wemid, green, TS 35
1040800000	WDU 2.5N ZQV	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1040880000	WDU 2.5N ZQV BL	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, Wemid, blue, TS 35
1730940000	WDU 2.5N/600UL	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35